15

20



NT APPLICATION

28

## WHAT IS CLAIMED IS:

1. A method of processing a request for a data communications session in a data network, comprising:

determining whether there is sufficient bandwidth to 5 accommodate the session in an initial cell associated with the request;

determining a set of cells contiguous or near to the initial cell to which the session may be transferred during the pendency of the session;

determining whether the selected set of cells have 10 sufficient bandwidth to support a decision to admit the session; and

admitting the session to the initial cell if there is sufficient bandwidth in the initial cell and the identified contiguous cells.

- The method of Claim 1 wherein the step of 2. determining whether or not there is sufficient bandwidth in the initial cell comprises the step of adding a fraction of the current bandwidth usage of the cell with a fraction of the historic bandwidth usage of the cell.
- The method of Claim 1 wherein the step of 3. identifying contiquous cells comprises a step 25 identifying contiguous cells to which the session may travel by identifying cells previously occupied by the user.
- The method of Claim 3 wherein the step of identifying cells previously occupied by the 30 comprises the step of identifying the percentage of time in which the user resides in a particular cell.



- The method of Claim 1 wherein the step of 5. determining a set of cells comprises the calculating a percentage likelihood that user requesting the session will affect each of predetermined number of cells and comparing percentages to a random number and selecting the set of cells responsive to the comparison.
- 10 6. The method of Claim 1 wherein the step of determining whether the selected set of cells have sufficient bandwidth comprises the step of calculating a probability that a user requesting the session will enter a given cell and multiplying the probability by the requested bandwidth to yield a probabilistic weighted bandwidth and comparing the probabilistic weighted bandwidth to the actual available bandwidth in the given cell.
- 20 7. The method of Claim 1 and further comprising:
  storing in a data base for a plurality of potential
  users of the network a data set representing the historic
  usage pattern of each of the plurality of users with
  respect to the percentage of calls which affect a
  25 plurality of numbers of cells.





30

8. The method of Claim 1 and further comprising:
determining if the user requesting the service has
ever resided in the initial cell or the contiguous or

near cells; and

- if the user has not resided in the initial cell or the contiguous cells, assigning a new user probability profile to the user prior to calculating the available bandwidth.
- 9. The method of Claim 1 wherein the step of determining whether the selected set of cells have sufficient bandwidth comprises the step of determining the available bandwidth at a contiguous or near cell by combining a fraction of the actual bandwidth available for that cell with a fraction of the historic bandwidth usage at that cell at a predetermined period of time in the future.
- The method of Claim 1 wherein the step set of cells comprises the step 20 determining a generating a random probability fraction and adding the transit cell probabilities associated with a particular the random probability is exceeded user until including all the cells identified within the identified number of transits from the initial cell within the set 25 of cells identified.

- 11. A data communications system comprising:
- a plurality of base transceiver stations each station associated with a cell;

a resource manager in communication with each of the base transceiver stations and operable to perform an admission control decision upon request from the base transceiver stations, the admission control decision comprising the steps of:

determining whether there is sufficient bandwidth to

10 accommodate the session in the initial cell associated
with the request;

determining a set of contiguous set of cells contiguous to the initial cell to which the session may be transferred during the pendency of the session;

determining whether the contiguous cells have sufficient bandwidth to service the session; and

admitting the session to the initial cell if there is sufficient bandwidth in the initial cell and the identified contiguous cells.

20

15

12. The system of Claim 11 wherein the resource manager is operable to store and use a table of data comprising historic usage information for a plurality of users of the system.

25

13. The system of Claim 12 wherein the historic usage information comprises information associated with the cells in the system most frequently occupied by the user.



14. The system of Claim 12 wherein the historic usage information associated with the number of cells affected by calls made by each of the plurality of users.

32

- 5 15. The system of Claim 11 wherein the resource manager is operable to store and use a table of data comprising historic bandwidth usages information for a plurality of cells in the system.
- 16. The system of Claim 15 wherein the usage information comprises usage information associated with usage levels at different times of day.
- 17. The system of Claim 15 wherein the usage information comprises usage information associated with usage levels at different day of the week.